

Cloud Web Application Firewall (WAF) CyberRisk Validation Report – Prophaze Business WAF

Product Version: Business

Published: November 10, 2022

Revision 1.1 12/6/2022

Report Contents:

1	Intro	oduction	2
2	Test	ing parameters and results	4
3	Seci	ırity Efficacy	5
	3.1	OWASP Score	5
	3.2	Bot Attacks	.7
	3.3	Layer 7 DoS Attacks	8
	3.4	Resiliency Score	.9
	3.5	Web Application Protection	.9
	3.6	WAF Vulnerability Assessment	10
4	Ope	rational efficiency	11
	4.1	Ease of Deployment	12
	4.2	Ease of Management	13
	4.3	Ease of Risk Management	14
	4.4	Scalable and elastic	14
	4.5	Logging, Monitoring, and Auditing	15
	4.6	False Positive Avoidance	15
5	Diffe	erentiators	16
6	Арр	endix	16
	6.1	Cloud WAF Test Deployment	16
	6.2	Test Execution	17
	6.3	Attack Types	18
	6.4	Prophaze Web Application Firewall Configuration	
	6.5	Prophaze Web Application Firewall Rules:	18
	6.6	Vendor Participation	19
	6.7	MITRE Mapped OWASP Attacks	20
	6.8	Deduped OWASP Score Calculation	20
7	Con	tact Information	21
8	Сор	yright and Disclaimer	21

Complete Security Score Operational Efficiency Score 85% Prophaze Average

Figure 1. Overall Validation Results for Prophaze Business Cloud Web Application Firewall

SecureIQLab completed testing for 14¹ of the leading enterprise class cloud web application firewall (WAF) products to determine their security efficacy and operational efficiency. Testing was conducted in accordance with the standards of the Anti-Malware Testing Standards Organization² (AMTSO). The test used version 2.0 of the SecureIQLab Cloud WAF CyberRisk Validation Methodology (AMTSO Test ID: AMTSO-LS1-TP054).

This report discusses the test results for the Software as a Service (Saas) Prophaze Business Plan Web Application Firewall. Test results for group minimums, averages and maximum results are also provided in certain categories for additional insight. Because thousands of attacks were simulated during the test, test results have necessarily been simplified and presented for review in a summary format. Figure 1 provides a summary of the product's overall validation results.

Bring Your Own Device (BYOD) and the remote workforce have dissolved the network perimeter and expanded the enterprise attack surface. Cost savings and operational simplicity drive organizations to adopt cloud-native and cloud-driven application architectures. These cloud-native and cloud-driven application architectures include API-driven, multi-tenant and multiuser applications.

The ubiquitous adoption of the cloud is not without challenges. Web application-based vulnerabilities are among the top breach vectors³ and threats to our cloud and hybrid environments are on the rise. Cloud-based web application firewalls (WAFs) are designed to protect web applications without interrupting business continuity in the cloud-first world. This test of cloud WAFs is intended to evaluate these products' effectiveness in mitigating these challenges.

In this cloud WAF test we measured effectiveness by subjecting products under test to a battery of diverse attacks. We secured cloud applications with the cloud WAFs we were testing. The cloud applications we secured included simple Ecommerce applications, multiuser web applications and applications with known vulnerabilities.

³ https://www.verizon.com/business/resources/reports/dbir/2021/masters-guide/summary-of-findings/



 $^{^{}m 1}$ Testing was attempted on a total of 17 cloud WAF solutions. See appendix section 6.6 for details.

² https://www.amtso.org/

These cloud applications were then used as attack targets. This allowed us to obtain empirically validated data based upon industry frameworks and regulations such as the OWASP Top 10⁴, MITRE ATT&CK and PCI DSS 4.0⁵.

This report covers testing for just 1 of the 14 products. An overview comparative report generally covering all 14 products is also available. Additionally, reports are available for the other 13 products tested.

In addition to cloud WAFs, SecureIQLab has also identified the following critical technologies for cloud security:

- Advanced Cloud Firewall (ACFW)
- Application Programming Interface (API) Security
- Extended Detection and Response (XDR)
- Internet of Things (IoT) Security
- Security Service Edge (SSE) and Secure Access Service Edge (SASE)

Because these technologies are critical for cloud security, SecurelQLab will test, evaluate and publish its findings about products in the above categories in upcoming tests.

SecureIQLab is a cloud security testing lab that was founded in 2019 and works with enterprises, governments, and security vendors to bridge the applied intelligence gap that exists between market analysis and technology research. SecureIQLab provides services to operationalize security and define metrics to help organizations improve their return on security investments and lower risk.

The Anti-Malware Testing Standards Organization (AMTSO) is an international non-profit association that focuses on addressing the industry need for improvement in the objectivity, quality, and relevance of cybersecurity testing methodologies. SecureIQLab is a member of AMTSO.

The Open Web Application Security Project (OWASP) is a nonprofit foundation that works to improve the security of software. "Through community-led open-source software projects, hundreds of local chapters worldwide, tens of thousands of members, and leading educational and training conferences, the OWASP Foundation is the source for developers and technologists to secure the web." It publishes the OWASP Top 10 Report. SecureIQLab has no affiliation with OWASP.

Prophaze was founded in 2019 and is a rising vendor in the WAF market. Prophaze's Business cloud WAF product was selected for inclusion in this test because it meets the SecurelQLab WAF validation methodology selection criteria.⁷

⁷ New market entrants and interested participating vendors with breakthrough technology offerings



⁴ Open Web Application Security Project®.

⁵ Payment Card Industry Data Security Standards.

⁶ https://owasp.org/

2 TESTING PARAMETERS AND RESULTS

Cloud-based web application firewalls (WAFs) should accurately detect, prevent, and log attack attempts while avoiding false positives. The majority of the attacks conducted against the cloud WAF product under test were tactics and techniques identified by OWASP for the exploitation of applications. SecureIQLab believes that attack tactics and techniques should be blocked, not just those with malicious payloads. For example, replacing the payload of "evil.com" with "hello world" doesn't change the fact that an attack technique was missed in some cases in order to avoid potential false positives. SecureIQLab's testing demonstrates the efficacy of the Prophaze Business WAF in this area.

Tests were performed utilizing black-box and gray-box testing. Black-box testing assumes that the internal code structure of the product being tested is unknown to the tester. For this testing approach, testers are not required to know a system's implementation details. Gray-box testing assumes that part of the product's internal code structure is known to the tester.

Default configurations and rule sets were used for the majority of the products in this test. However, any "Detect Only" mode settings that were part of default configurations were modified to "Block" mode, with default rulesets used as applicable.

Tuning a WAF can be complex. Tuning was based on industry and marketplace expectations that these solutions will require minimal to no tuning during provisioning, deployment, and management phases, which translates to lower operational expenses and increased revenue for the targeted audience, i.e., SMBs, managed service providers (MSPs), and managed security service providers (MSSPs).

Further, any required tuning was performed (1) according to vendor recommendations publicly available on the Prophaze's website and (2) according to relevant documentation available on Prophaze's documentation site to align with the customer experience during the deployment and management of the product. (Enterprises are advised to exercise due diligence during this process to avoid impacting business.)

WAF-protected applications were used during testing by performing standard user transactions that included form submissions, comment writing, ecommerce transactions, and other transactions. See Appendix Section 6 for additional information on the configurations utilized during this test.

More detailed information about our testing methods is contained in version 2.0 of the SecureIQLab <u>Cloud WAF</u> <u>CyberRisk Validation Methodology</u> (AMTSO Test ID: AMTSO-LS1-TP054).



3 **SECURITY EFFICACY**




Figure 2. Security Validation Results for Prophaze Business Web Application Firewall

Figure 2 above provides an overview of the SecureIQLab findings during the security validation of the Prophaze WAF. The *Complete Security Score* depicts the average of all five security categories tested, minus any duplicated data in the *OWASP Score*. Equation 1 below depicts the *Complete Security Score* calculation. In this equation, the *Deduped OWASP Score* is the *OWASP Score*, from section 3.1, with the A02, A04, A06, and A09 vulnerability results excluded to avoid duplicating data.

$$\frac{Complete \ Security}{Score} = \frac{\left(\begin{array}{c} Dedupted \\ OWASP \ Score \end{array} + \begin{array}{c} Bot \ Attack \\ Score \end{array} + \begin{array}{c} Layer \ 7 \ DoS \\ Score \end{array} + \begin{array}{c} Resiliency \\ Score \end{array} + \begin{array}{c} Vulnerable \\ Environment \\ Score \end{array} \right)}{5}$$

Equation 1. Calculation of Complete Security Score

Every cloud WAF evaluated in this test was subjected to fourteen different categories of more than 400 real world-based operational scenarios targeting small-to-medium businesses and enterprises alike. Over 9100 attacks were used encompassing these scenarios and categories. The depth and scope of the testing performed by SecurelQLab carries on our tradition of innovation and improvement. SecurelQLab will continue to add attack libraries and other relevant operational metrics in future iterations of this test.

3.1 OWASP Score

The Open Web Application Security Project (OWASP) is a non-profit foundation dedicated to improving web application security⁸. The OWASP Top 10⁹ Report is assembled by security experts from across the globe and describes the most critical web application vulnerabilities. This year's testing is based on the OWASP Top 10 2021.



⁸ SecureIQLab is not affiliated with OWASP.

⁹ https://owasp.org/www-project-top-ten/

The Prophaze WAF was tested against nine of the OWASP Top 10 vulnerabilities. The OWASP A08:2021 – Software and Data Integrity Failures vulnerability was not included in testing because it relates to coding and infrastructure practices that are outside the scope of WAF security.

For detailed explanations of each of these attacks, please reference the OWASP Top 10. Table 1 below provides the results from these tests.

OWASP.	Pro	Prophaze Test Results			Group Test Results		
	Test Case	# Attacks	# Blocked	%Blocked or Score	Test Minimum	Test Average	Test Maximum
A01 Broken Access Control	CSRF	4	0	0%	0%	<mark>16%</mark>	100%
	Path Traversal	3977	2307	58%	48%	92%	100%
A02 Cryptographic Failures	Feature to implement SSL certificates	NA		100%	100%	100%	100%
A03 Injection	CRLF	103	3	3%	0%	28%	100%
	Cross Site Scripting	2691	2632	98%	3 %	87%	100%
	Host Header Injection	10	2	20%	0%	47%	100%
	HTML injection	5	5	100%	0%	40%	100%
	LDAP injection	46	46	100%	<mark>15%</mark>	94%	100%
	OS injection	324	251	77%	23%	71%	97%
	SQL Injection	1549	1319	85%	31%	70%	97%
	SSTI	123	107	87%	<mark>4</mark> %	67%	100%
	Xpath	16	11	69%	0%	47%	88%
A04 Insecure Design	Web scraping bot	1	0	0%	0%	86%	100%
A05 Security Misconfiguration	Unrestricted File Upload	36	0	0%	0%	75%	100%
	XXE	122	0	0%	0%	41%	100%
A06 Vulnerable and Outdated Components	Web Application CVEs	20	11	55%	55%	74%	90%
A07 Identification and Authentication Failures	Credential Stuffing Brute force attack	1	0	0%	0%	36%	100%
A09 Security Logging and Monitoring Failures	Logging, monitoring and provided by WAF	NA	NA	80%	60%	80%	93%
A10 Server-Side Request Forgery (SSRF)	SSRF	15	2	13 <mark>%</mark>	0%	50%	100%
OWASP Score			•	85%	75%	88%	96%

Table 1. OWASP Vulnerability Testing

Category averages are determined by equally weighting the test case averages within each category. As an example, Equation 2 below provides the formula for calculating the average for the *A01 Broken Access Control* vulnerabilities category.

$$\frac{A01 \; Broken}{Access \; Control} \; = \frac{\left(\begin{array}{c} \% \; Path \; Traversal \\ Attacks \; Blocked \\ \end{array} + \begin{array}{c} \% \; CSRF \\ Attacks \; Blocked \\ \end{array} \right)}{2}$$

Equation 2. Formula for Calculating the average for A01 Broken Access Control vulnerabilities OWASP category

The OWASP Score is derived from averaging A02 Cryptographic Failures Score with A09 Security Logging and Monitoring Failures Score, and the combined total block/the combined total attacks for A01 Broken Access Control, A03 Injection, A04 Insecure Design, A05 Security Misconfiguration, A06 Vulnerable and Outdated Components, A07 Identification and Authentication Failures, and A10 Server-Side Request Forgery (SSRF). Equation 3 provides the formula for the calculation of the OWASP Score.

$$OWASP = \frac{A02 + A09}{Score} + \frac{A09 + \frac{\left(\begin{array}{c} Total\ A01 + Total\ A03 + Total\ A03 + Total\ A04 + Total\ A05 + Total\ A06 + Total\ A07 + Total\ A10}{Attacks + Attacks + Attacks + Attacks + Attacks + Attacks + Attacks + Attacks} \\ \left(\begin{array}{c} Total\ A01 + Total\ A03 + Total\ A04 + Total\ A05 + Total\ A06 + Total\ A07 + Total\ A10}{Blocked \quad Blocked \quad Blocked \quad Blocked \quad Blocked \quad Blocked \quad Blocked} \\ \left(\begin{array}{c} Total\ A01 + Total\ A03 + Total\ A04 + Total\ A05 + Total\ A06 + Total\ A07 + Total\ A10}{Attacks \quad Attacks \\ \end{array} \right)$$

Equation 3. Calculation of OWASP Score






Figure 3. OWASP Sore Visual

The OWASP Score visual, Figure 3, shows how the results for the Prophaze WAF (blue bar) compares to the minimum score from the test group (red line), the average score from the test group (yellow line) and the maximum score from the test group (green line). The gray vertical left and right lines mark 0% and 100% respectively.

Please see appendix section 6.7 for information regarding mapping the OWASP test cases to the MITRE ATT&CK Enterprise Framework.¹⁰

3.2 BOT ATTACKS

For purposes of this test, a bot is defined as an automated tool that is used by a remote attacker to carry out automated attacks. The bot tool can exist on the attacker's computer or a compromised endpoint. Prophaze's Business Web Application Firewall was tested against seven types of bot attacks. These attacks were initiated from Asian and North American locations to determine whether the geolocation of an attack source impacts the product's security effectiveness. Results show that geolocation does not impact the product's security effectiveness. Six different bot attacks were used while testing. The results and these attacks are mapped in Table 2 to the MITRE ATT&CK framework, as far as possible. The *Bot Score* is calculated by averaging the seven contributing scores. The maximum *Bot Attack Score* for the tested vendors was 100%. The minimum *Bot Attack Score* for the tested vendors was 17%.



¹⁰ SecureIQLab is not affiliated with The MITRE Corporation.

4		ATT&CK [®] Enterprise Technique	es	Prophaze	Test Group
Bot Attacks	MITRE Tactic	MITRE Technique	Sub-techniques	Test Results	Average Results
Broken Link Checker	Reconnaissance ID: TA0043	Search Victim-Owned Websites ID: T1594	NA	Blocked	36%
L7 DOS with TOR network	Impact ID:TA0040	Endpoint Denial of Service ID: T1499	Application or System Exploitation T1499.004	Bypass	86%
Login Bruteforce	Credential Access ID: TA006	Brute Force ID: T1110	Password Spraying ID: T1110.003	Bypass	50%
User Agent Manipulation	Reconnaissance ID: TA0043	Gather Victim Host Information ID: T1592	Client Configurations ID: T1592.004	Bypass	43%
Web Scraping	Reconnaissance ID: TA0043	Search Open Websites/Domains ID: T1593 Gather Victim Org Information ID: T1591	Search Engines ID: T1593.002 Identify Business Tempo ID: T1591.003	Bypass	50%
Website crawler	Reconnaissance ID: TA0043	Search Open Websites/Domains ID: T1593 Gather Victim Org Information ID: T1591 Active Scanning ID: T1595	Search Engines ID: T1593.002 Identify Business Tempo ID: T1591.003 Wordlist Scanning ID: T1595.003	Blocked	36%
Bot Score		•		33%	50%

Table 2. Bot Attack Results with Attacks Mapped to MITRE ATT&CK

3.3 LAYER 7 DOS ATTACKS

Layer 7 Denial-of-Service (DoS) attacks are more difficult to detect than other DoS layer attacks because they use a valid TCP connection. Test cases for such attacks are also more infrastructure friendly than Distributed Denial-of-Service (DDoS) attacks and thus avoid the issues that DDoS attacks may trigger with cloud service providers. Below, Table 3 presents the results of testing the Prophaze Business WAF against five Layer 7 DoS attacks and maps these attacks to the MITRE ATT&CK framework, as far as possible. The product's *Layer 7 DoS Score* was determined by taking the average of its scores against the five attacks. The highest Layer 7 DoS Score of the group of tested vendors in this category was 100% and the lowest rating was 40%.

Layer 7 DoS	Prophaze	Test Group		
Layer / DUS	Test Results	Average Results		
DoS Attack	Bypass	64%		
Slow DoS Attack	Blocked	93%		
Slow DoS Attack	Blocked	93%		
Slow DoS Attack	Blocked	79%		
Slow DoS Attack	Blocked	79%		
Layer 7 DoS Score	80%	81%		

Table 3. Layer 7 DoS Validation

Table 4 shows how the attacks used in the resiliency test cases map to the MITRE ATT&CK framework.

ATT&CK* Enterprise Techniques				
MITRE Tactic	MITRE Technique	Sub-techniques		
Impact	Endpoint Denial of Service	Application or System Exploitation		
ID:TA0040	ID: T1499	T1499.004		

Table 4. Layer 7 DoS Attacks Mapped to MITRE ATT&CK



3.4 RESILIENCY SCORE

Security products must demonstrate resiliency. Failure to do so will have significant consequences. The prevailing definition of operational resilience is provided by the Department of Defense (DoD), and states it is: "The ability of systems to resist, absorb, and recover from or adapt to an adverse occurrence during operation that may cause harm, destruction, or loss of ability to perform mission-related functions." ¹¹

To test its operational resilience, The Prophaze Business WAF was tested against 71 total test cases using 25 unique evasive methods were employed to determine whether it could successfully block attacks that would otherwise go unseen. A higher resiliency score indicates a product is more capable of withstanding and absorbing different variations of attacks while a lower resiliency score indicates a product is less likely to detect different variations of attacks.

Table 5 below provides the test cases, the Prophaze Business Web Application Firewall results and maps these attacks to the MITRE ATT&CK framework, as far as possible. The *Resiliency Score* is the percentage of attacks blocked out of the total 71 attacks. The maximum *Resiliency Score* for the tested vendors was 90%. The minimum *Resiliency Score* for the tested vendors was 17%.

	Prophaze	Test Group
Resiliency	Test Results	Average Results
Cross Site Scripting	90%	84%
HTML Injection	71%	39%
OS Command Injection	73%	50%
SQL Injection	82%	62%
Unrestricted File Uploads	0%	79%
XXE	0%	47%
Resiliency Score	68%	63%

Table 5. Resiliency Validation Results

Table 6 shows how the attacks used in the resiliency test cases map to the MITRE ATT&CK framework.

ATT&CK® Enterprise Techniques				
MITRE Tactic	MITRE Technique			
Defense Evasion	Obfuscated Files or Information			
ID: TA0005	ID: T1027			

Table 6. Resiliency Attacks Mapped to MITRE ATT&CK

3.5 WEB APPLICATION PROTECTION

A cloud-based WAF should protect vulnerable web applications. While the proliferation of web application frameworks has made deployment and maintenance of web applications simpler, it has also made it challenging to update these frameworks without affecting the functionality of the web applications. Businesses, MSPs and MSSPs can ill afford downtime and may delay updates to avoid breaking applications. Consequently, applications can remain vulnerable to various known vulnerabilities and exploits. This makes it easier for cybercriminals and script kiddies to compromise these applications.



¹¹ https://csrc.nist.gov/glossary/term/operational resilience

The Prophaze Business Cloud WAF was tested against known exploits on 20 different vulnerable applications. See Table 7 below for the full results. The Vulnerable Environment Score is percentage of attacks blocked out of the 20 attacks. The highest Vulnerable Environment Score of the group of tested vendors in this category was 90% and the lowest rating was 55%.

₩ Vulnerable	Prophaze	Test Group	
Environment	Test Results	Average Results	
Apisix	100%	79%	
Confluence	100%	100%	
Django	25%	50%	
Flink	0%	68%	
Ghostscript	0%	29%	
Grafana	100%	100%	
Log4J	100%	100%	
Metabase	100%	93%	
OpenTSDB	100%	71%	
PhpMyAdmin	100%	100%	
Rails	0%	79%	
Shiro	0%	50%	
Solr	100%	100%	
Struts2	100%	93%	
Uwsgi	100%	100%	
Vulnerable Environment Score	55%	75%	

Table 7. Vulnerable Web Environment Results

Table 8 shows how the attacks used in the vulnerable environment test cases map to the MITRE ATT&CK framework.

ATT&C	CK° Enterprise Techniques
MITRE Tactic	MITRE Technique
Inital access ID: TA0001	Exploit Public-Facing Application ID: T1190

Table 8. Vulnerable Environment Attacks Mapped to MITRE

3.6 WAF VULNERABILITY ASSESSMENT

Security solutions, regardless of their deployment method, should not increase the attack surface of the environments that they are designed to protect. Additionally, privileges often granted to security solutions, should not be exploitable by threat actors. In another groundbreaking test, SecureIQLab has assessed the security of the cloud WAF product itself.

Prophaze's Business WAF was tested against 9 vulnerability assessment techniques that are commonly used to assess the hardness of applications. Table 9 provides the details of our findings and maps key areas of these attacks to the MITRE ATT&CK framework where possible. All WAFs assessed passed the WAF Vulnerability Assessment.



WAF Vulnerability Assesment		ATT&C	K [®]	Prophaze Results	Group Average
IDOR - Insecure Direct Object Reference	Reconnaisance ID: TA0043	Gather Victim Host Information: Software ID: T1592	Software DI: T1592.002	Blocked	Blocked
Cross Site Scripting	Initial Access ID: TA0001	Drive-by Compromise ID: T1189	NA	Blocked	Blocked
Server Side Request Forgery	Credential Access ID: TA0006	Forge Web Credentials ID: T1606	NA	Blocked	Blocked
Privilege Escalation	Privilege Escalation ID: TA0004	Valid Accounts ID:T1078	NA	Blocked	Blocked
Hard Coded Values (URLs, IDs, Passwords etc)	NA	NA	NA	Blocked	Blocked
Back Button Enabled	NA	NA	NA	Blocked	Blocked
Insecure Session Management	Privilege Escalation ID: TA0004	NA	NA	Blocked	Blocked
Sensitive Data Exposure	Reconnaisance ID: TA0043	Active scanning ID: T1595	Vulnerability Scanning ID: T1595.002	Blocked	Blocked
Weak SSL Ciphers	NA	NA	NA	Blocked	Blocked
WAF Vulnerability Assesment Score				Pass	Pass

Table 9. WAF Vulnerability Assessment




Figure 4. Validation of Operational Efficiency for Prophaze Business Web Application Firewall

Cloud-based WAF technology allows for the creation of customized security, which benefits organizations in the following ways:

- Ease of deployment and integration
- Less complex to manage
- Ease of risk management
- Scalable and elastic



- Monitoring, logging, and control capabilities
- Allows business-related transactions

Prophaze's Business Web Application Firewall was validated in each of these areas of operational efficiency. Figure 4, above, displays the product's high-level results.

Category scores were calculated by aggregating earned points and then dividing this number by the total number of possible points to find a percentage. Points (integers 0-3) are earned for each feature within a category as follows:

- High or Yes (Green) = 3 Points
- Med (Yellow) = 2 Points
- Low (Orange) = 1 Point
- NA/No (Red) = 0 Points

The *Operational Efficiency Rating* was calculated by adding together the total points for each category, then dividing this number by the maximum potential points (114) and multiplying that number by 100%. Equation 4 states the *Operational Efficiency Score* calculation.

$$\frac{Operational}{Efficiency} = \frac{\begin{pmatrix} Ease \ of \\ Deployment \ + \ Management \ + \ Management \ + \ Management \ + \ and \ Elastic \ + \ Auditing \\ Points \ Points \ Points \ Points \ Points \end{pmatrix}}{114 \ points} \times 100\%$$

Equation 4. Operational Efficiency Rating Calculation

The mode for each feature validated is used to calculate the test group feature results. Group test averages were then calculated by adding the modes for each feature and then dividing this number by the total number of possible points to find a percentage.

4.1 EASE OF DEPLOYMENT

Cloud WAFs typically take less than an hour to a few days to set up and seldom require installation of custom software or hardware.

Cloud WAFs should integrate with other security tools, Security Information and Event Management (SIEM) systems, and data repositories. This typically allows both tasks and alerts to be automated. Typical integrations include DevOps tools like Slack and Jira and can include automated additions to policies as threats are detected.

SecureIQLab validated the ease of deployment and integration for the Prophaze WAF. The overall simplicity of the deployment was high. A minimal understanding of AWS resources a prerequisite for deployment. Findings for deployment and ease of integration are in Table 10 below.



Food of Donloyment	Prophaze	Test Group	
Ease of Deployment	Validation Results	Average Results	
Simplicity of Provisioning	High	Med	
Ease of Setting Up WAF Service	High	Med	
Ease of Certificate Creations and Management	High	Med	
Application Load Balancing and Monitoring	High	High	
Deployment Autonomy/Customer Support Experience	High	High	
Integration with Multi-Cloud WAF	Yes	Yes	
Plug and Play Integration with On-prem Firewall	Yes	No	
Plug and Play Integration for SIEM/S3 Bucket	Yes	Yes	
Plug and Play Integration for API Gateway	Yes	Yes	
Rating	100%	78%	

Table 10. Deployment and Ease of Integration Findings

Earning 27 of the possible 27 points gave Prophaze a 100% *Ease of Deployment Rating*. The highest rating of the group of tested vendors in this category was 100% and the lowest rating was 56%.

4.2 EASE OF MANAGEMENT

Cloud WAFs market the promise that they are more easily managed than on-premises solutions. They are less complex and more easily managed because they receive automated updates, automatically deal with spikes in traffic (as discussed below) and work out of the box.

Cloud WAFs are less complex because the cloud WAF provider manages the security details and automatically allocates the resources needed. The cloud WAF provider typically has already tuned the security software. Users typically have a single management console to monitor.

Users can typically create additional policies that allow identity-based access and network segmentation. Because the cloud WAF provider automatically applies policy modifications wherever the cloud WAF is deployed, policy modification is generally simple and rapid. Results from SecureIQLab's experience while managing Prophaze's WAF are in Table 11, below.

Coop of Monogoment	Prophaze		Test Group		
Ease of Management	Validation Res	ults	Average Results		
Simplicity of Tuning WAF	Med		High		
Intuitiveness Security Policy	High		High		
Ease of Managing Security Policy	Med		High		
Customization of Dashboard	Low		High		
Capability of Asset Management	Med		Low		
Facilitation of PCI Compliance	Med		Med		
Facilitation of Data Sovereignty (GDPR)	High		High		
WAF Update Automation	Med		Med		
Simplicity of Managing Web ACL	Med		High		
Single Sign On Support	No		Yes		
Rating	63%		87%		

Table 11. Ease of Management Rating

Earning 19 of the possible 30 points gave Prophaze a 63% *Ease of Management Rating*. The highest rating of the group of tested vendors in this category was 97% and the lowest rating was 63%.



4.3 EASE OF RISK MANAGEMENT

Today's enterprises typically incorporate an Enterprise Risk Management (ERM) program, and Ease of Risk Management is an integral category within such program. In the context of cybersecurity solutions, such as a Cloud WAF, deployed within an enterprise, it is imperative that organizations measure some of the Key Performance Indicators (KPI's) associated with risk management while deploying, managing, and operating such solutions.

These KPI's should then be aggregated such that significant cyber threats form a big picture of the enterprise's risks. Risk management should align with format and measurement scales that can be compared to other types of operational risks.

Table 12 provides SecureIQLab's Ease of Risk Management Rating. The higher the Ease of Risk Management Rating, the easier it is to manage security threats and business continuity risks. This in turn lowers the solution's operational overhead and its hidden costs of ownership.

Ease of Risk Management	Prophaze	Test Group	
	Validation Results	Average Results	
Business Continuity Management	High	Low	
Risk Assessment & Mitigation	Med	High	
Security Metrics Reporting	Med	Med	
Threat Analytics Dashboard	Med	Med	
Alert and Rule Management	Low	High	
Automated Alert and Rule Management	Med	High	
Incident Management	High	High	
Rating	71%	67%	

Table 12. Ease of Risk Management Rating

Earning 15 of the possible 21 points gave Prophaze a 71% *Ease of Risk Management Rating*. The highest rating of the group of tested vendors in this category was 95% and the lowest rating was 57%.

4.4 SCALABLE AND ELASTIC

Cloud WAFs should help the customer avoid sizing issues planning by providing for automated flexible scaling. Scaling typically occurs in response to changing traffic load patterns. Providers typically allow customers to choose options that balance optimizing performance and optimizing costs. Table 13 highlights SecurelQLab's findings in this area.

Scalable and Elastic Capabilities	Prophaze	Test Group	
	Validation Results	Average Results	
Load Balancing and Failover Capability	Med	Med	
Auto-Scaling Capability	Yes	Yes	
Manual Scaling Capability	No	Yes	
Designed for Static and Dynamic Sites	Yes	Yes	
Multi-tenancy Support	Yes	Yes	
Rating	73%	93%	

Table 13. Scalable and Elastic Validation

Earning 11 of the possible 15 points gave Prophaze a 73% *Scalable and Elastic Compatibilities Rating*. The highest rating of the group of tested vendors in this category was 100% and the lowest rating was 67%.



4.5 LOGGING, MONITORING, AND AUDITING

Sufficient logging capabilities are required for incident response, auditing, and many compliance and regulatory purposes. Cloud WAFs need to provide enough visibility into web traffic and sufficient control capabilities for security teams to spot issues and resolve them. Additionally, Cloud WAFs need to have a means to integrate logged data with other storage devices for redundancy. Below, Table 14 covers our logging, compliance and auditing findings.

Logging and Auditing Capabilities	Prophaze		Test Group	
	Validation Results		Average Results	
Log Configuration Simplicity	High		High	
Log Storage Capability	High		High	
Web Request Inspection	High		Med	
Application Monitoring	Med		Med	
Infrastructure Monitoring	NA		High	
Auditing Capability	Low		High	
Multi-Factor Authentication	No		Yes	
Rating	57%		90%	

Table 14. Log and Audit details

Earning 12 of the possible 21 points gave Prophaze a 57% *Logging and Capabilities Rating*. The highest rating of the group of tested vendors in this category was 95% and the lowest rating was 57%.

4.6 FALSE POSITIVE AVOIDANCE

WAFs need to allow business-related transactions while blocking malicious activity. The false positive rate is important because false positives interfere with the operation of the business. Policies need to be adjusted to minimize false positives. False Positives increase alerts for already stretched thin security teams and contribute to alert fatigue.

Properly tuned security devices will not detect benign traffic as malicious. Over 300 different false positive test cases were used to validate that the product under test (PUT) would not block simulated consumer purchases. These test cases simulated users that would browse the web application normally while being protected by the cloud WAF. Blocking legitimate user activity constitutes a false positive, increases the operational burden for the enterprise and would require additional tuning to correct. The results for the *False Positive Avoidance* testing are found below in Table 15. Prophase's *False Positive Avoidance Score* is the percentage of the total allowed legitimate activity test cases to the total possible 308 test cases. Prophaze allowed 303 out of 308 test cases for a score of 98.4%. False positives decrease operational efficiency. The higher the *False Positive Avoidance Score*, the less impact on the operational efficiency.

False Positives	Prophaze	Test Group	
	Test Results	Average Results	
False Positive Avoidance Score	98.4%	95.5%	

Table 15. False Positive Avoidance Results

The highest *False Positive Avoidance Score* of the group of tested vendors in this category was 100.0% and the lowest score was 81.2%. The *False Positive Avoidance Score* will be used in the calculation of the Return on Security Investment (*ROSI*) in the 2022 comparative report.



5 DIFFERENTIATORS

SecureIQLab testers and analysts research the products under test and work to determine key differentiators for the Prophaze WAF from other cloud WAFs. Information in this section is sourced from hands on experience, customer feedback and from vendor subject matter experts.

- Simple user experience.
- Requires minimal experience to configure and manage.
- Ingress controller for Kubernetes.
- Kubernetes native.

6 APPENDIX

6.1 CLOUD WAF TEST DEPLOYMENT




Figure 5. WAF deployment diagram

The cloud WAF was deployed with default policy with an elastic load balancer to protect the web-applications on AWS, see Figure 5. All web-application transactions were inspected by the cloud WAF. In doing so, the cloud WAF was expected to provide protections against threats that were originated by the malicious actors while allowing authorized users to access the web application resources.

During deployment, our engineers noted the time it took to deploy with out of the box controls and the complexity of the deployment. Also noted was whether our engineering team was required to contact the WAF vendor's support team to successfully complete the WAF deployment. See Table 10 for deployment findings.



6.2 **TEST EXECUTION**

SecureIQLab performed security validation using crafted attacks that are relevant to today's cloud application hosted on cloud and cloud native applications. SecureIQLab carefully curated such attacks via research generated by our own red team as well as the attacks that are prevalent in the wild. Open-source tool kits were also utilized while performing this assessment.

Before the testing was conducted, SecureIQLab validated that the cloud WAF solution was in an operational state by verifying the following:

Connection Validation:

Before any test was conducted, SecureIQLab ensured that the Cloud WAF could be accessed by the administrator and was passing normal application traffic. This was to ensure that any dynamic content such as IP blacklist protection could be updated on regular basis by the cloud WAF.

Logging:

SecureIQLab asserts that logging is a critical and a crucial component while running a cloud WAF. SecureIQLab verified that the cloud WAF being tested had sufficient administrative as well as attack logging to ensure Security Analysts could troubleshoot and fix issues as required.

Updates:

Protocol updates in the form of rules, signatures and reputations were applied as they became generally available. SecureIQLab made best efforts to apply these updates to products prior to their evaluation.

The above processes were repeated wherever applicable throughout the test. Once the deployment of Prophaze's WAF solution and baseline testing were completed, the security validation testing began.

The first phase of attack was to gather information and perform reconnaissance against the application. The was done to gather as much information as possible to be utilized when penetrating the target during the vulnerability assessment and exploitation phases. SecureIQLab performed vulnerability analysis using automated tools such as Burpsuite and Nessus in addition to performing manual analysis. The main objective of vulnerability analysis is to discover flaws in the systems and applications which can be leveraged by an attacker. These flaws ranged anywhere from host and service misconfiguration to insecure application design. Vulnerability Analysis was based on:

- 1. Active Scan: Active scan involves direct interaction with the component being tested for security vulnera-
- 2. Passive Scan: Passive scan involves meta-data analysis and traffic monitoring.

Once information gathering and reconnaissance was completed, we began exploitation as the next phase in this process. Penetration testing was critical in the evaluation of cloud WAF technologies.

Once exploited, "post-exploitation" was undertaken. Post-exploitation refers to the actions taken after the initial compromise of a system or device. It often describes the methodical approach of using privilege escalation or pivoting techniques—which allowed SecureIQLab, in this case, to establish a new source of attack from the new vantage point in the system—to gain additional access to systems or network resources. We demonstrate the risk presented by exploitable systems and what post-exploitation may likely occur with web applications.

Additionally, defense evasion is an important tool in an attacker's arsenal. This allows old methods and techniques to be repurposed to evade protection against attacks which might otherwise get blocked by the Cloud WAF. More details on these techniques are covered in the Resiliency section.



The testing demonstrates the effectiveness of the PUT to protect vulnerable assets from targeted threats and exploitation. This asset/target and threat-based approach forms the basis from which PUT security effectiveness is measured.

6.3 ATTACK TYPES

The SecureIQLab threat and attack suite contains attacks (including mutations of the same underlying attacks) and proprietary exploits harvested through our test harness or crafted by our threat research team. SecureIQLab has a number of complex web applications which have also been constructed to include known vulnerabilities and coding errors. Groups of exploits are carefully selected from this library to test based on the intended attack. Each exploit has been validated to impact the target vulnerable host(s) by compromising the asset, which can range from being the web server, the web application or sites.

The level of compromise can vary between instigating a denial-of-service (DoS) condition, providing administrator/root access to the host server, allowing malicious users to amend system parameters or application data before submission, browse and/or retrieve files stored on the host server, escalating user privileges, and so on.

6.4 Prophaze Web Application Firewall Configuration

Prophaze's Business Web Application Firewall was deployed and configured according to the instructions found in the *Free Trail guide* 12 .

6.5 PROPHAZE WEB APPLICATION FIREWALL RULES:

Prophaze's Business Web Application Firewall was configured per Prophaze's default configuration.



¹² https://dash.prophaze.com/register

6.6 Vendor Participation

Table 16 lists the test status for each of the 17 vendors that SecureIQLab attempted to evaluate in this test iteration.

Vendor	Test Status
Akamai	Testing Completed
AWS	Testing Completed
Microsoft	Testing Completed
Barracuda	Testing Completed
Citrix	Evaluation terminated due to product issues ¹³
Cloudflare	Testing Completed
F5	Testing Completed
Fastly	Evaluation terminated by vendor ¹³
Fortinet	Testing Completed
Google	Testing Completed
Imperva	Testing Completed
Oracle	Testing Completed
Prophaze	Testing Completed
Radware	Evaluation terminated by vendor ¹³
StackPath	Testing Completed
Sucuri	Testing Completed
Wallarm	Testing Completed

Table 12. Vendor Test Status



¹³ Contact SecureIQLab for details

6.7 MITRE MAPPED OWASP ATTACKS

Table 17 maps attacks used in the test from the OWASP to the MITRE ATT&CK Enterprise Framework.

(7) OWASP.	ATT&CK°			
Оошнон	Tactic	Technique	Sub-technique	
CRLF Injection	Discovery ID: TA0007			
xss	Initial Access ID: TA0001	Drive-by Compromise ID: T1189		
CSRF	Credential Access ID: TA0006	Forge Web Credentials ID: T1606		
Host Header Injection	Execution ID: TA002	User Execution ID: T1204	Malicious Link ID: T1204.001	
HTML Injection	Execution ID: TA002	User Execution ID: T1204	Malicious Link ID: T1204.001	
LDAP Injection	Discovery ID: TA0007	Domain Trust Discovery ID: T1482		
OS Command Injection	Defense Evasion ID: TA005 Execution ID: TA0002	Indirect Command Execution ID: T1202 Command and Scripting Interpreter ID: T1059	Unix Shell ID: T1059.004	
Path Traversal	Discovery ID: TA0007	File and Directory Discovery ID: T1083		
SSTI	Defense Evasion ID: TA005	Template Injection ID: T1221		
SQL Injection	Initial Access ID: TA0001	Exploit Public-Facing Application ID: T1190		
SSRF	Credential Access ID: TA0006	Forge Web Credentials ID: T1606		
Unrestricted File Upload	Defense Evasion ID: TA005	Masquerading ID: T1036		
XXE	Execution ID: TA002	User Execution ID: T1204	Malicious Link ID: T1204.001	
Xpath	Initial Access ID: TA0001	Drive-by Compromise ID: T1189		

Table 17. OWASP ATTACKS TO MITRE ATT&CK

6.8 DEDUPED OWASP SCORE CALCULATION

Equation 5 demonstrates the calculation of the *Deduped OWASP Score*.

$$\frac{Deduped}{OWASP}_{Score} = \frac{ \left(\begin{array}{c} Total \ A01 \\ Attacks \\ Blocked \\ Score \end{array} + \begin{array}{c} Total \ A03 \\ Attacks \\ Attacks \\ Blocked \\ Attacks \\ A$$

Equation 5. Deduped OWASP Score Calculation



7 CONTACT INFORMATION

SecureIQLab, LLC. 6001 W. Parmer Lane Ste 370, #970 Austin, TX 78704 USA

+1.512.575.3457

www.secureiqlab.com info@secureiqlab.com

8 COPYRIGHT AND DISCLAIMER

This publication is Copyright © 2022 by SecureIQLab®. Any use of the results, etc., in whole or in part, is ONLY permitted after the explicit written agreement of SecureIQLab prior to any publication. SecureIQLab cannot be held liable for any damage or loss, which might occur as result of, or in connection with, the use of the information provided in this paper. We take every possible care to ensure the correctness of the basic data, but a liability for the correctness of the research results cannot be taken by any representative of SecureIQLab. We do not give any guarantee of the correctness, completeness, or suitability for a specific purpose of any of the information/content provided at any given time. No one else involved in creating, producing or delivering research results shall be liable for any indirect, special or consequential damage, or loss of profits, arising out of, or related to, the use or inability to use, the services provided by the website, research documents or any related data.

For more information about SecureIQLab and the testing methodologies, please visit our website.

SecureIQLab (November 2022)



^{1.1} Corrected typos and added section 6.8 Deduped OWASP Score Calculation.